

UM981

GPS/BDS/GLONASS/Galileo/QZSS
All-Constellation Multi-Frequency
RTK/INS Integrated Positioning
Module



17.0 × 22.0 × 2.6 mm



CE FC IC

Features

- » Based on Unicore's proprietary GNSS SoC NebulasIV that integrates RF, baseband and high-precision algorithm
- » All-constellation multi-frequency RTK engine and advanced RTK technology
- » Instant RTK initialization technology
- » Excellent anti-jamming and anti-spoofing capabilities, supporting jamming detection and spoofing detection
- » Heading2 technology to provide orientation information
- » STANDALONE single-station high-precision positioning technology
- » Supports B2b-PPP and E6-HAS
- » On-board MEMS integrated positioning technology to ensure continuous positioning when loss of lock on GNSS signals occurs

Applications



Precision Agriculture

UM981 is Unicore's new-generation proprietary RTK and INS integrated navigation module. It can simultaneously track multiple satellite systems and frequencies, including GPS, BDS, GLONASS, Galileo, QZSS, NavIC and SBAS. The module integrates a high-speed floating point processor and an RTK dedicated coprocessor, being able to output positioning data at 100Hz. The on-board MEMS chip and U-Fusion integrated navigation algorithm ensure continuous positioning when loss of lock on GNSS signals occurs, providing high-quality positioning results in complex environments such as building blocks, tunnels, overpasses and tree shades. UM981 is designed for high-precision navigation and positioning applications and is ideal for high-precision agriculture applications.

Physical Characteristics

Packaging	54 pin LGA
Dimension	17.0 × 22.0 × 2.6 mm
Weight	1.91 g ± 0.03 g

Environmental Specifications

Operating Temperature	-40°C ~ +85°C
Storage Temperature	-55°C ~ +95°C
Humidity	95% No condensation
Vibration	GB/T 28046.3, ISO 16750-3
Shock	GB/T 28046.3, ISO 16750-3

Communication Interfaces

3 x UART(LVTTL)
1 x I ² C*
1 x SPI*
1 x CAN*

Note: Items marked with * are supported by specific firmware.

Performance Specifications

Channel	1408 channels, based on NebulasIV			
Frequency	GPS L1C/A, L1C, L2C, L2P(Y), L5 BDS B1I, B3I, B1C, B2a, B2b GLONASS G1, G2, G3 Galileo E1, E5a, E5b, E6 QZSS L1C/A, L1C/B, L1C, L2C, L5, L6 NavIC L5 SBAS L1C/A			
Single Point Positioning(RMS)	Horizontal: 1.5 m	Time Accuracy (RMS)	20 ns	
	Vertical: 2.5 m	Velocity Accuracy (RMS)	0.03 m/s	
DGPS (RMS)	Horizontal: 0.4 m	Cold Start	< 12 s	
	Vertical: 0.8 m	Initialization Time	< 5 s (typical)	
RTK (RMS)	Horizontal: 0.8 cm + 1 ppm	Initialization Reliability	> 99.9%	
	Vertical: 1.5 cm + 1 ppm	Data Update Rate	100 Hz IMU raw data 50 Hz* RTK	
PPP (RMS)	Horizontal: 5cm			
	Vertical: 10 cm			
Attitude Accuracy	Heading	Roll	Pitch	
	0.3°	0.2°	0.2°	
Positioning Error of INS only	< 5 % of the distance traveled without GNSS signals			
Observation Accuracy (RMS)	BDS	GPS	GLONASS	Galileo
B1I/B1C/L1C/A/G1/E1 Code	10 cm	10 cm	10 cm	10 cm
B1I/B1C/L1C/A/G1/E1 Carrier Phase	1 mm	1 mm	1 mm	1 mm
B2I/B2a/B2b/L5/G3/E5a/E5b Code	10 cm	10 cm	10 cm	10 cm
B2I/B2a/B2b/L5/G3/E5a/E5b Carrier Phase	1 mm	1 mm	1 mm	1 mm
B3I/L2P(Y)/L2C/G2/E6 Code	10 cm	10 cm	10 cm	10 cm
B3I/L2P(Y)/L2C/G2/E6 Carrier Phase	1 mm	1 mm	1 mm	1 mm
Differential Data	RTCM V3.X			
Data Format	NMEA 0183, Unicore			